

HYDRAULIC HITCH

Operates with pilot or full system pressure

Wear indicators

Positive Mechanical Lock (Triple Lock)

Complies with Australian (AS4772-2008) and International (ISO13031.2) Hydraulic Quick Hitch Standards



Rated lifting point

Wear indicators

Locking circuit operates with pilot or full system pressure

TILTING HYDRAULIC HITCH

Complies with Australian (AS4772-2008) and International (ISO13031.2) Hydraulic Quick Hitch Standards

Hydraulic Hose Guard Plate

Positive Mechanical Lock (Triple Lock)

Rated lifting point



INCLUDES

CERTIFIED LIFTING POINT



PATENTED LOCKING SYSTEM



180° TILT RANGE



VISUAL LOCKING INDICATOR



WEAR RESISTANT STEEL



SINGLE ACTION LOCK



FULLY COMPLIANT



BUILT TO MACHINE SPECS



QUEENSLAND
PH: (07) 3376 3177
sales@normeng.com.au
787 Boundary Road
Darra QLD 4074

VICTORIA
PH: (03) 9775 1965
vicsales@normeng.com.au
2/45 Frankston Gardens Drive
Carrum Downs VIC 3201

NEW SOUTH WALES
PH: (02) 7246 7838
nswsales@normeng.com.au
2/3 Contaplas Street
Arndell Park NSW 2148

NEW ZEALAND
PH: (64) 7889 7080
service@normeng.co.nz
14/2582 State Highway 26
Morrinsville 3375 NZ